

[illegible]

Technical drawing of a vertical assembly, likely a door or panel, showing dimensions and components.

Dimensions:

- Overall height: 970^{+2}_{-0}
- Overall width: 221
- Top section height: 524
- Bottom section height: 30
- Bottom section width: 15
- Bottom section width: 19
- Bottom section width: 5
- Bottom section width: 35
- Bottom section width: 35

Labels:

- 裏補強材(t15)
- 前棧木

[illegible]

Technical drawing of a door threshold cross-section. The drawing shows a threshold with a total width of 780⁺¹₋₃ mm. The height of the threshold is 21 mm, with a 15 mm section for the plate and a 6 mm section for the filler. The thickness of the plate is t15. The threshold is secured with M4 flat washers (ユニクローム) and M4x18 Torx head screws (ユニクローム). The filler is polyurethane resin (ポリウレタン樹脂充填). The threshold is also secured with a special adhesive (専用接着剤). The distance from the edge of the plate to the center of the screw is 10 mm. The distance from the center of the screw to the edge of the threshold is 7 mm. The total length of the threshold is 850 mm or less.

780⁺¹₋₃

ポリウレタン樹脂充填

専用接着剤

21

15 6

7

10

合板 t15

M4 平ワッシャー
ユニクローム

M4x18 トラス頭タッピングネジ
ユニクローム

取付金具(SU-21 t2.3)

850以内

製品名 HS780型アンダー樹脂シンク取付標準図 (YFBカウンター Lタイプ)	尺 度	1/2 1/5
--	--------	---------

吉本産業株式会社