

Technical drawing of a kitchen sink with dimensions and labels.

Left View (Top View):

- Overall width: 562
- Overall height: 462
- Corner radius: 4-R10
- Mounting hole diameter: $\phi 38$

Right View (Front View):

- Overall width: 780 (カウンター開口)
- Overall height: 525 (カウンター開口)
- Mounting hole diameter: $\phi 38$
- Distance from top edge to mounting hole center: 430
- Distance from bottom edge to mounting hole center: 430
- Distance from left edge to mounting hole center: 810⁺¹₋₃
- Distance from right edge to mounting hole center: 810⁺¹₋₃
- Distance from top edge to sink rim: 370
- Distance from bottom edge to sink rim: 385
- Distance from left edge to sink rim: 555⁺¹₋₃
- Distance from right edge to sink rim: 555⁺¹₋₃
- Distance from top edge to sink rim: 45
- Distance from bottom edge to sink rim: 60

Technical drawing showing a cross-section of a container. The drawing includes the following dimensions and labels:

- Overall height: 970^{+2}_{-0}
- Internal height: 510
- Label: 裏補強材(t15)
- Label: 前棧木
- Dimensions (from bottom to top): 15, 19, 6, 29, 35
- Bottom width: 254

Technical drawing showing the installation details of a sink, including dimensions and component labels.

Dimensions:

- Overall width: 970^{+2}_{-0}
- Counter opening: カウンター開口 525
- Sink maximum size: シンク最大寸法 555^{+1}_{+3}
- Water stop hole position: 水栓穴位置 430
- Front flange width: 前栈木 35
- Back flange width: 裏補強材(t15) 360
- Mounting bracket width: 取付金具(SUZ t1.6) M4x6 ナベ頭小ネジ 38
- Mounting bracket height: 7
- Mounting bracket thickness: 15
- Mounting bracket depth: 19
- Mounting bracket width: 60
- Mounting bracket height: 45
- Mounting bracket depth: 31
- Mounting bracket width: 8

Labels:

- ポリウレタン樹脂充填 (Polyurethane resin filling)
- 専用接着剤 (Special adhesive)
- 裏補強材(t15) (Back reinforcement material (t15))
- 前栈木 (Front flange)
- 取付金具(SUZ t1.6) M4x6 ナベ頭小ネジ (Mounting bracket (SUZ t1.6) M4x6 hex head small screw)
- 水栓穴位置 430 (Water stop hole position 430)

Technical drawing of a wall-to-ceiling joint assembly. The drawing shows a cross-section of a wall and ceiling. Key components labeled include: **ポリウレタン樹脂充填** (Polyurethane resin filling), **専用接着剤** (Special adhesive), **合板 t15** (Plywood t15), **M4 平ワッシャー ユニクローム** (M4 flat washer UniChrome), **M4x18 トラス頭タッピングネジ ユニクローム** (M4x18 truss head tapping screw UniChrome), and **取付金具 (SU-21 t2.3)** (Mounting bracket SU-21 t2.3). Dimensions are provided: 810 (+1/-3) for the total width, 21 for the bracket height, 15 and 6 for the bracket segments, 7 for the adhesive layer, 20 for the bracket base, and 864 for the total length. A break line is shown in the middle of the assembly.

製品名 HS810型アンダー樹脂シンク取付標準図 (YFBカウンター Rタイプ)	尺 度	1/2 1/10
--	--------	----------

吉本産業株式会社